



# CPD50L1

## 4-WHEEL LI-ION COUNTERBALANCE FORKLIFT 5.0T

5000 kg 6000 mm 80 V Li-Ion



The CPD50L1 counterbalance forklift is suitable for heavy duty, even the most demanding applications, thanks to the various lithium battery options and the improved travel speed.

It can deliver great performance to various industries, such as beverage, wood, metal, construction and others. For handling materials in containers, the CPD50L1 with a dedicated mast can fully meet the need due to its proper overhead guard height of 2250mm.

SPECIFICATION	REF	UNIT	VALUE
Battery type			Li-Ion
Battery nominal capacity K5		Ah	560
Battery voltage		V	80
Rated capacity	Q	kg	5000
Load centre distance	c	mm	500
Service weight		kg	7000
Height, mast lowered	$h_1$	mm	2230
Lift	$h_3$	mm	3000
Height, mast extended	$h_4$	mm	4175
Overall length		mm	3970
Overall width	$b_1/b_2$	mm	1550
Length to face of forks	l2	mm	2900
Fork dimensions	s/e/l	mm	55X150X1070
Turning radius		Wa	2675
Manufacturer			EP
Model designation			CPD50L1

# Features

## New appearance combining both practical and aesthetics design

The new design of the CPD50L1 reflects both practicality and beauty. The internal lay-out has been optimized, resulting in shorter l2 of 2900mm and a tighter turning radius of 2675mm. The compact size makes it easy to maneuver in confined spaces. The bolted overhead guard offers maximum flexibility for retrofit or replacement and the height of 2250mm combined with triplex 4,5 meters elevation allows for goods transportation in standard containers.



## Different lithium battery capacity options to meet different needs

The CPD50L1 offers two lithium battery options, 80V/560Ah and 80V/690Ah, to meet regular and intensive applications. It is designed around the advantages of lithium technology - opportunity charging, zero maintenance, zero carbon emissions and zero gas emissions during charging, which contributes to convenient and sustainable operation. The practical IP65 external plug provide charging convenience without the need to open the cover.



## Fast travel speed for maximum efficiency

Compared to the classic CPD50F8, the travel speed of the CPD50L1 is improved to 16/18km/h, speeding up warehouse turnover and increase transport efficiency.





## Joystick option for fatigue-free operation

The CPD50L1 can be fitted with hydraulic joystick controls instead of mechanical levers. Positioned at the end of the armrest, fingertip operation is possible, improving the operator ergonomics with the following controls: all fork hydraulic control including the 4th way, driving direction (F-N-B), horn, emergency stop button.

## Market-proven components and optimized layout

The CPD50L1 inherits mature components, such as drive unit, motors, controllers and mast, ensuring great reliability. The box girder structure is more rigid granting higher stability and the new hydraulic pump makes the lifting operation more precise and quiet.



## Ergonomic seat for a comfortable experience



The seat height (h7) is 1208mm from the ground, lower in its category. This makes it easy for the driver to get in and out

## VDI Chart


	SPECIFICATION	REF	UNIT	VALUE
1.1	Manufacturer			EP
1.2	Model designation			CPD50L1
1.3	Drive			Electric
1.4	Operator type			Seated
1.5	Rated capacity	Q	kg	5000
1.6	Load centre distance	c	mm	500
1.8	Load distance, centre of drive axle to fork		mm	548
1.9	Wheelbase		mm	2000
2.1	Service weight		kg	7000
2.2	Axle loading, laden front/rear		kg	10840/1160
2.3	Axle loading, unladen front/rear		kg	3220/3780
3.1	Tyres			Solidrubber

SPECIFICATION		REF	UNIT	VALUE
3.2	Tyre size, front		mm	28x12.5-15
3.3	Tyre size, rear		mm	23X10-12
3.5	Wheels, number front/rear (x=drive wheels)			2x/2
3.6	Tread width, front	b <sub>10</sub>	mm	1262
3.7	Tread width, rear	b <sub>11</sub>	mm	1085
4.0	Max lift height	H	mm	6000
4.1	Tilt of mast/fork carriage forward/backward		°	6/ 10
4.2	Height, mast lowered	h <sub>1</sub>	mm	2230
4.3	Free lift		mm	150
4.4	Lift	h <sub>3</sub>	mm	3000
4.5	Height, mast extended	h <sub>4</sub>	mm	4175
4.7	Height of overhead guard (cabin)		mm	2250
4.8	Seat height relating to SIP/stand height		mm	1208
4.12	Coupling height		mm	555
4.19	Overall length		mm	3970
4.20	Length to face of forks	l <sub>2</sub>	mm	2900
4.21	Overall width	b <sub>1</sub> /b <sub>2</sub>	mm	1550
4.22	Fork dimensions	s/e/l	mm	55X150X1070
4.23	Fork carriage ISO 2328, class/type A, B			3A
4.24	Fork carriage width		mm	1250
4.31	Ground clearance, laden, below mast		mm	130
4.32	Ground clearance, centre of wheelbase		mm	150
4.34.1	Aisle width for pallets 1000×1200 crossways		Ast	4440
4.34.2	Aisle width for pallets 800 × 1200 crossways		Ast	4640
4.35	Turning radius		Wa	2675
5.1	Travel speed, laden/unladen		km/h	16/18
5.2	Lift speed, laden/unladen		m/s	0.3/0.46
5.3	Lowering speed, laden/unladen		m/s	0.45/ 0.51
5.8	Max. gradeability, laden/unladen		%	15/20
5.10	Service brake			Hydraulic/Mechanical
5.11	Parking brake			Mechanical
6.1	Drive motor rating S2 60 min		kW	18
6.2	Lift motor rating at S3 15%		kW	25.4
6.4	Battery nominal capacity K5		Ah	560

	SPECIFICATION	REF	UNIT	VALUE
6.4	Battery voltage		V	80
6.4.1	Battery type			Li-Ion
6.5	Battery weight		kg	396
6.6	Energy consumption according to DIN EN 16796		kWh/h	14.38 <sup>1)</sup>
6.7	Turnover output according to VDI 2198			300
6.8	Turnover efficiency according to VDI 2198			23.77
8.1	Type of drive unit			AC
10.7	Sound pressure level at the driver's seat		dB(A)	70



## CAPACITY CHART



## Mast Options

MAST TYPE	LIFT HEIGHT (H3, MM)	MAST LOWERED HEIGHT (H1, MM)	MAST EXTENDED HEIGHT, NO BACKREST (H4, MM)	MAST EXTENDED HEIGHT, WITH BACKREST (H4, MM)	FREE LIFT HEIGHT, NO BACKREST (H2, MM)	FREE LIFT HEIGHT, WITH BACKREST (H2, MM)
2-standard mast	3000	2233	4175	3770	145	145
2-standard mast	3300	2383	4475	4070	145	145
2-standard mast	3500	2483	4675	4270	145	145
2-standard mast	3700	2583	4875	4470	145	145
2-standard mast	4000	2783	5175	4770	145	145
2-standard mast	4250	2908	5425	5020	145	145
2-standard mast	4500	3033	5675	5270	145	145
2-free mast	2710	2200	3885	3480	1055	1355
2-free mast	3000	2345	4175	3770	1200	1500
2-free mast	3300	2495	4475	4070	1350	1650
2-free mast	3500	2595	4675	4270	1450	1750
3-free mast	4000	2080	4780	5200	1230	900
3-free mast	4350	2195	5130	5550	1345	1015

MAST TYPE	LIFT HEIGHT (H3, MM)	MAST LOWERED HEIGHT (H1, MM)	MAST EXTENDED HEIGHT, NO BACKREST (H4, MM)	MAST EXTENDED HEIGHT, WITH BACKREST (H4, MM)	FREE LIFT HEIGHT, NO BACKREST (H2, MM)	FREE LIFT HEIGHT, WITH BACKREST (H2, MM)
3-free mast	4500	2245	5280	5700	1395	1065
3-free mast	4700	2310	5480	5900	1460	1130
3-free mast	5000	2460	5780	6200	1610	1280
3-free mast	5500	2680	6280	6700	1830	1500
3-free mast	6000	2845	6780	7200	1995	1665

## Options

ITEM	OPTIONS (optional items marked in yellow)
Fork dimension	150*55*1070   150*55*1220   150*55*1370   150*55*1520   150*55*1670   150*55*1820
Fork lowered height	1200   Yes and can be customized
Fork carriage width option	1250mm   Yes and can be customized
Front wheel material	Solid   Non-marking solid
Rear wheel material	Solid   Non-marking solid
Battery capacity	80V560AH   80V690AH
Charger	80V200A   80V150A
Battery display indicator (BDI)	With time
Seat type	Premium   Premium + seatbelt logic switch   Suspension   Suspension + seatbelt logic switch
Attachments	No   Built-in sidershifter   External shifter   Fork positioner
Traction pin	Yes
Front lamp	LED
Rear lamp	No   LED
Warning lamp	Yes
Blue lamp	No   2 front   1 rear   2 front + 1 rear
Area warning lamp	No   Red, 1 left + 1 right
Rearview mirror	1 rearview mirror   Add 1 on both sides
Buzzer	Yes
OPS system	Yes
Telematics	No   Yes and not customized

ITEM	OPTIONS (optional items marked in yellow)
Cabin	No   Basic semi-cabin   Upgrade semi cabin   Full cabin
Turn signal light	Yes